# Leica DISTO™ D510

The original laser distance meter

\*\*Bluetooth\*\*

| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 199.826\*\*
| 19

# 精確定位及可靠的戶外測量!

Swiss Technology
by Leica Geosystems

Leica DISTO™ D510代表簡單輕鬆的室外 距離測量。獨特的數位取景器與360°傾角感 測器,一般機種無法測量的遠距離也能夠勝 任。此外內建藍芽,並可搭配聰明的免費應 用APP,為未來做好了準備。

## 功能特色:

DISTO"D510

- 四倍放大數位取景器
- IP65等級防塵防水
- 360°角度感測器
- 智慧水平模式
- 懸高測量
- 智慧藍芽
- 免費APP Leica DISTO™ sketch







#### 簡單精確的定位

Leica DISTO™ D510使用4倍變 焦的取景器,即使在強光下的室 外難以看見雷射點,利用數位取 景,便可直接在顯示器上便可對 準目標。



#### 堅固且容易清潔的本體

按鍵與外殼特別密封處理,防水 防塵,可直接在水中清洗也沒有 問題。無論天候多麼惡劣,仍然 能夠完成工作。



#### Leica DISTO™ D510

- Leica DISTO™ D510
- 皮套
- 手繩
- 電池



#### 無限可能的測量選項

Leica DISTO™ D510配備360° 傾角感測器,能夠測量角度,更 可同時測量水平距離。結合數位 取景功能,提供更多間接測量的 可能。



#### 智慧藍牙與應用APP

測量數據可透過藍芽進行傳輸。 搭配Leica DISTO™ sketch能夠 支援iPhone / iPad,直接進行現 場繪製,簡單操作毫不費力。

# 技術規格 Technical Data

測量精度	± 1 mm
測量範圍	0.05 - 200 m
測量單位	m, ft, in, yd
傾角感測器	360°
彩色顯示幕.取景器	4x zoom
傳輸介面	Bluetooth® Smart
免費應用APP	Leica DISTO™ sketch
電力供應	Type AA × 2
產品尺寸	122 × 55 × 31 mm
紀錄	30組
自動多功能底板	•

### 功能 Functions

距離測量	傾斜跟蹤
智慧水平模式	面積/體積
懸高測量	加法/減法
高度剖面	放樣功能
放樣功能	傾斜跟蹤
斜邊測量	梯形斜邊
長距離模式	計算機

\*) System requirements & details at www.disto.com



All illustrations, descriptions and technical specifications are subject to change without prior notice. Printed in Switzerland. Copyright Leica Geosystems AG, Heerbrugg, Switzerland, 2012.

Leica Geosystems AG Heerbrugg, Switzerland www.leica-geosystems.com



Laser class 2 in accordance with IEC 60825-1



Register your device within 8 weeks of purchase at www.leica-geosystems.com/registration and extend your no cost period to 3 years.

Dealer Stamp





